

HSCC (India) Limited
as Executing Agency on behalf of
MINISTRY OF HEALTH & FAMILY WELFARE,
Government of India, New Delhi

Date: 30.08.2018

AMENDMENT No. – I

Project Name: Tender for Office Furniture and other associated works for Super Specialty Block at Jhansi, Latur and Udaipur under PMSSY-III.

Tender no: HSCC/PMSSY-JLU/Office-Fur/ 2018, **dated:** 17.08.2018.

This has reference to the subject works, the reply to the queries raised by the bidders during the pre-bid meeting held at HSCC Corporate Office, Noida on 28.08.2018 at 15:00 hrs is enclosed at Annexure I, which shall be treated as a part of tender to be submitted online duly signed & stamp along with tender.

All other terms & Conditions of the Tender shall remain unchanged.

Prospective bidders are advised to regularly scan through HSCC e-tender portal <http://www.tenderwizard.com/HSCC> and <http://www.hsccltd.co.in> as corrigendum/amendments etc., if any, will be notified on this portal only and separate advertisement will not be made for this.

Sr. CGM-II,
HSCC (India) Ltd.

Amendment-I**Tender for Office Furniture and other associated works for Super Specialty Block at Jhansi, Latur and Udaipur under PMSSY-III.**

Tender no: HSCC/PMSSY-JLU/Office-Fur/ 2018

Reply to queries received during the Pre-Bid Conference held on 28.08.2018 at 15:00 hrs

S.No.	Cl.No./ Item No./ Specification / Vol./ Ref.	Original Specifications	Bidders Queries	Reply / Clarification
1	Vol-III, Item No. 07 3 Seater Waiting Chair	Armrest, leg and bracket: Die casting aluminium alloy with polish treatment and sprayed with static powder. Seat and back: high density Polyurethane (PU) with metal frame inside. Fire retardant moulded PU foam. Beam: high intensity hexagonal metal tube, with superior load-bearing capacity and stability.	Please confirm if legs, armrest and bracket can be considered in MS powdercoated.	As per Tender Condition Only
2	Vol-III, Item No. 11 Centre Table	The Top is Made up of Toughened Glass and the leg is made up of Chrome Plated Undresturure. Overall size of the corner table is 550(W)x550(D)x 510(H)	Centre Table & Corner Table – Size mentioned is same for both, please correct	Overall size of the center table is 1100(W)x550(D)x 510(H) and corner table is 550(W)x550(D)x 510(H).
3	Vol-III, Item No. 18 Almirah	Almira shall have an overall size of 916mm(W)x486mm(D)x1980mm(H) with welded construction. It should have the shelf thickness of 0.7 mm, Back thickness of 0.8mm, Door thickness of 0.8mm (high yield strength) and all other components shall have a thickness of 0.9mm. These components shall be made of CRCA 'D' grade high yield strength as per IS:513. The Storwel Plain should have a Mazak handle and three way locking mechanism with Shooting Bolts. It should have a height wise adjustable shelf mounting which shall have a Uniformly Distributed Load Capacity of max 40 Kg. It should also have a M10 Screw type Leveller with Hex plastic base. The finishing shall include Epoxy powder coated to the thickness of 50 microns (+/- 10). Plenty of colour options and shelving options shall be available.	Please confirm if required in welded construction or can be quoted for knock down construction as well.	As per Tender Condition Only

Amendment-I**Tender for Office Furniture and other associated works for Super Specialty Block at Jhansi, Latur and Udaipur under PMSSY-III.**

Tender no: HSCC/PMSSY-JLU/Office-Fur/ 2018

Reply to queries received during the Pre-Bid Conference held on 28.08.2018 at 15:00 hrs

S.No.	Cl.No./ Item No./ Specification / Vol./ Ref.	Original Specifications	Bidders Queries	Reply / Clarification
4	Vol-III, Item No. 32 WORKSTATIONS (1200 x 600)mm	<p>Providing and placing panel& tile based modular workstation, with partition thickness as 65-70 mm thick and height - 1200 including powder coated aluminium trims. Tiles: Combination of tiles could be metal, laminate, fabric and tack able.</p> <p>Wire Management - Wires shall be taken into the system through cable ducts from the junction boxes and it is carried up to the panels through concealed conduits inside the blocks.</p> <p>Side legs - Metal powder coated legs at the end and shared condition or gable end made of particle board should also be considered.</p> <p>Work surface - Made out of 25 mm thick prelam particle board with 2mm thick pvc lipping edge banding. The size of work table should be of size 1200mm W x 600mm D</p> <p>Pedestals with legs –Pedestal made of particle board of 18mm thick ,Free Standing central locking and of size 390 mm width x 435 mm depth x 646 mm height 3dr = 2box+1file.</p> <p>CPU trolley - with castors KBPT made of metal.</p> <p>Note: All partitions and side panels have levelling screws for adjustment in case of Uneven floor to take care of +/- 10 mm of uneven flooring.</p>	Please amend partition thickness from 65-70 mm, as the industry standard for workstation partition thickness is 55-60 mm	As per Tender Condition
				Sr. Mgr. (C), HSCC (India) Limited